

## MS51844 Series COPPER (SL2-) and ALUMINUM (SL1-)

- Sleeves for eye, lap and stop sleeve splicing are available in either aluminum or copper in a wide variety of sizes ranging from .03125 – 0.5000" inclusive.
- All oval sleeves (copper or aluminum) are capable of supporting a greater load than the rated breaking strength of the cable to which they are attached when properly applied with Locoloc® Hand Swager to bare cable on 3×7, 7×7, 7×19, and 6×19 constructions
- Copper oval sleeves available either plain, zinc, nickel, or tin plated.  
Plain copper supplied unless otherwise specified
- Special lengths of either copper or aluminum oval and stop sleeves available on special order.



SPECIFICATIONS:  
CONFORMS TO MIL. SPEC. MS51844

To Fit Cable Diameter		Aluminum Oval Sleeves	Copper Oval Sleeves			Use Tool Number
			Plain	Zinc-Plated	Tin-Plated	
1/32	Part No.	Available in Copper Only	SL2-1	SL2-1P	SL2-1TP	000-WCI, #1-3-SBHS, or #5-H
	MS Part No.		MS51844-40	MS51844-20	MS51844-80	
	Weight lbs/Mpcs		.6			
3/64	Part No.	SL1-1.5	SL2-1.5	SL2-1.5P	SL2-1.5TP	00-WCI, 0-1.5-3FS, #1-3-SBHS, 0-3/64SC, or #5-H
	MS Part No.		MS51844-41	MS51844-21	MS51844-81	
	Weight lbs/Mpcs	.6	2			
1/16	Part No.	SL1-2	SL2-2	SL2-2P	SL2-2TP	000-WCI, 0-1.5-3FS, #1-3-SBHS, 0-1/16SC, #1-BSC, #1-P, HC, SL7NDK-R, or #5-H
	MS Part No.		MS51844-42	MS51844-22	MS51844-82	
	Weight lbs/Mpcs	.8	2.5			
3/32	Part No.	SL1-3	SL2-3	SL2-3P	SL2-3TP	0-1.5-3FS, 0-3/32SC, #1-3-SBHS, #1-SC, #1-P, #1-BSC, SL-7NDK-R, or #5-H
	MS Part No.		MS51844-43	MS51844-23	MS51844-83	
	Weight lbs/Mpcs	2.5	6			
1/8	Part No.	SL1-4	SL2-4	SL2-4P	SL2-4TP	0-1/8SC, #1-SC, #1-BSC, #1-P, SL-7NDK-R, or #5-H
	MS Part No.		MS51844-44	MS51844-24	MS51844-84	
	Weight lbs/Mpcs	5.8	16			
5/32	Part No.	SL1-5	SL2-5	SL2-5P	SL2-5TP	0-5/32SC, #1-SC, #1-BSC, #1-P, SL-&NDK-Rm or #5-H
	MS Part No.		MS51844-45	MS51844-25	MS51844-85	
	Weight lbs/Mpcs	7	23			
3/16	Part No.	SL1-6	SL2-6	SL2-6P	SL2-6TP	0-3/16SC, #1-SC, #1-BSC, #1-P, SK-7NDK-R, or #5-H
	MS Part No.		MS51844-46	MS51844-26	MS51844-86	
	Weight lbs/Mpcs	14.5	53			
7/32	Part No.	SL1-7	SL2-7	SL2-7P	SL2-7TP	0-7/32, SL-7NDK-R, or #5-H
	MS Part No.		MS51844-47	MS51844-27	MS51844-87	
	Weight lbs/Mpcs	21	45.5			
1/4	Part No.	SL1-8	SL2-8	SL2-8P	SL2-8TP	0-1/4, #3-H, SL-7NDK-R, SL-C7510, or #5-H
	MS Part No.		MS51844-48	MS51844-28	MS51844-88	
	Weight lbs/Mpcs	28	76			
9/32	Part No.	SL1-9	SL2-9	SL2-9P	SL2-9TP	0-9/32, SL-7NDK-R, or #5-H
	MS Part No.					
	Weight lbs/Mpcs					
5/16	Part No.	SL1-10	SL2-10	SL2-10P	SL2-10TP	0-5/16, #3-H, SL-7NDK-R, SL-C7510, or #5-H
	MS Part No.		MS51844-49	MS51844-29	MS51844-89	
	Weight lbs/Mpcs	41	122	124		
3/8	Part No.	SL1-12	SL2-12	SL2-12P	SL2-12TP	SL-C7510, #3-H, or #5-H
	MS Part No.		MS51844-50	MS51844-30	MS51844-90	
	Weight lbs/Mpcs	57	156	158		
7/16	Part No.	SL1-14	SL2-14	SL2-14P	SL2-14TP	SL-C7510, #3-H, or #5-H
	MS Part No.		MS51844-51	MS51844-31	MS51844-91	
	Weight lbs/Mpcs	116	282	284		
1/2	Part No.	SL1-16	SL2-16	SL2-16P	SL2-16TP	SL-C7510, #3-H, or #5-H
	MS Part No.		MS51844-52	MS51844-32	MS51844-92	
	Weight lbs/Mpcs	172	384	386		